

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - October 2024										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,285	1,930	2,537	26,003	17-9	18,0	8-9	
1.4307	304L	4307	2,285	1,930	2,537	26,003	18-8L	18,0	8-9	
1.4306	304L	4306	2,508	2,117	2,784	28,532	18-10L	18,0	10,0	
1.4541	321	4541	2,479	2,093	2,753	28,210	18-10Ti	17,0	9,0	
1.4401	316	4401	3,823	3,227	4,244	43,491	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	3,823	3,227	4,244	43,491	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	3,872	3,268	4,299	44,047	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,181	3,529	4,641	47,567	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,263	3,598	4,732	48,500	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,310	3,639	4,785	49,042	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	4,945	4,175	5,490	56,265	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,351	1,984	2,609	26,740	153MA™	18,5	9,5	
1.4845	310S	4845	4,009	3,384	4,452	45,616	25-20	25,0	20,0	
1.4833	309S	4833	3,025	2,553	3,357	34,405	23-13	22,0	12,5	
1.4835	S30815	253MA	2,654	2,240	2,946	30,191	253MA®	21,0	11,0	
1.4539	904L	904L	6,837	5,772	7,591	77,787	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	6,912	5,834	7,673	78,627	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	8,024	6,774	8,908	91,286	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,280	1,925	2,532	25,949	2304	23,0	4,5	
1.4462	S31803	2205	3,643	3,075	4,045	41,453	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,334	3,659	4,813	49,318	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,728	1,459	1,919	19,671	LDX2101®	21,0	1,5	
1.4828	-	4828	2,897	2,445	3,215	32,953	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,685	2,267	2,982	30,554	LDX2404™			
1.4003	S40977	4003	0,988	0,834	1,096	11,234	Ferritic			
1.4016	430	4016	1,125	0,950	1,249	12,800	Ferritic			
1.4509	441	4509	1,441	1,216	1,600	16,389	Ferritic			
1.4512	409	4512	0,946	0,799	1,051	10,767	Ferritic			
1.4521	444	4521	2,401	2,027	2,667	27,324	Ferritic			